

Battery Operated Pallet Truck

FIPL-BOPT-108



108 B



108 A

MODEL	FIPL-BOPT-108 A	FIPL-BOPT-108 B
Product Size		
Capacity (kg)	2500	1500
Min. fork height (mm)	90	90
Max. fork height (mm)	200	200
Lifting height (mm)	110	110
Fork length (mm)	1150/1220	1150/1220
Single fork width (mm)	160	160
width over all forks (mm)	550/685	550/685
Fork wheel – tandem (mm)	80x70 PU	80x70 PU
Support wheel (mm)	180x70 PU	-
Driving wheel (mm)	230x70 PU	150x55 PU
Turning Radius (mm)	1810	1810
Travel Speed (Loaded/Unloaded) (km/h)	4.5/5.5	4.5/5.5
Lifting Speed (Loaded / Unloaded) (mm/sec)	22/30	22/30
Lowering Speed (Loaded / Unloaded) (mm/sec)	28/24	20/18
Type of Control	Rider Stand on Platform	walkie
Traction Motor	24 V, 1.5 kW	24 V, 1 kW
Lift Motor	24 V, 2 kW	24 V, 1 kW
Battery - Voltage / Capacity	24V / 240 Ah	24V / 100 Ah
FEATURES	<ul style="list-style-type: none"> - Overload Protection through pressure relief valve - Operators Belly Switch for operator's protection - Jerk free lifting and lowering. - Cutoff limit at top height to save energy and motor overheating. 	

Note: There may be any specification/dimensional change. If these specifications are critical, the proposed application should be discussed.