

Center Cylinder / Boring Lift

FIPL-172-A



MODEL	FIPL-172-A	
Product Size		
Capacity (Kg)	1000 - 5000	As per requirement
Platform Size (W*L) (mm)	1000x1000 (Min.) - 6000x3000(Max.)	As per requirement
Min. Height (Can be flushed in pit) (mm)	1000 - 1200	As per requirement
Lifting Height (mm)	2000 - 10000	As per requirement
Power Pack	5 HP - 15 HP	As per requirement
Travel Speed (mm/sec.)	50 - 150	
Levels	G+1 / G+2 / G+3 / G+4 / G+5	As per requirement
Motor	3 Phase; ABB / BBL / Rotomotive / Siemens	As per requirement
Railings on Platform	4 Sides, 1000mm Height	As per requirement
Boring Dia and Height	Dia- 100mm-350mm; Depth - Lifting Height + 5 Feet As per requirement	
Features	<ul style="list-style-type: none"> - More/Bigger Space for platform - Jerk Free traveling - Two/Four side Guide Rollers - Used in Car Showrooms, Industries, Inside or Outside of buildings 	
Additional Features available	<ul style="list-style-type: none"> - Collapsible Doors / Auto Doors at Entry and Exit with Interlocking System - Excel type elevator locks in Collapsible doors. - Cabin instead of railings on platform. - Doors on platform. - MS Structure to Cover all sides of Goods Lift. - Blain Valves 	
*Tolerance in lifting and technical Specs. +/- upto 25mm		

Note: There may be any specification/dimensional change. If these specifications are critical, the proposed application should be discussed.