

High Rise Scissor Lift

FIPL-138



**Pneumatic / Solid
Rubber Tyre**



**AC/DC Hydraulic
Power-Pack**



**Emergency
Descending Valve**



**Operating Push
Button Station**



Maintenance Strut



Crane Lifting Hooks

Standard Configurations

- Auxiliary Lowering Device
- Anti -burst systems
- Adjustable outriggers
- Rain-proof Cabinet
- Emergency Stop Button

Optional Configurations

- Motorized Device
- Extension Platform (6-12m)
- DC power or both AC & DC power
- Solid Tyre
- Oversea Brand Hydraulic Pump System

High Rise Scissor Lift

FIPL-138



Model	FIPL-138/6	FIPL-138/7.5	FIPL-138/9	FIPL-138/11	FIPL-138/12	FIPL-138/14	FIPL-138/16	FIPL-138/6-10	FIPL-138/9-10	FIPL-138/12-10
S.W.L on Extension	500 kg	500kg	500 kg	500 kg	500 kg	500 kg	300kg	1000kg	1000kg	1000kg
Platform height max	6m	7.5m	9m	11m	12m	14m	16m	6m	9m	12m
Platform size (L*W)	1.85x0.88m	1.8x1.00m	1.8x1.00m	2.1x1.15m	2.45x1.35m	2.45x1.35m	2.75x1.5m	1.8x1.00m	1.8x1.25m	2.45x1.35m
Overall size (L*W*H)	2.07x1.04x1.45m	2.07x1.16x1.70m	2.07x1.16x1.87m	2.37x1.31x1.83m	2.72x1.51x1.83m	2.72x1.51x2.16m	3.02x1.68x2.70m	2.07x1.20x1.55m	2.07x1.45x1.87m	2.72x1.51x1.90m
Lifting time	54S	72S	80S	88S	90S	120S	130S	80S	100S	135S
Motor power	1.5kW	1.5kW	1.5kW	2.2kW	3kW	3kW	3kW	2.2kW	3kW	4kW
Power voltage	AC380V	AC380V	AC380V	AC380V	AC380V	AC380V	AC380V	AC380V	AC380V	AC380V
Weight	650kg	1100kg	1260kg	1380kg	1850kg	2150kg	2680kg	950kg	1510kg	2700kg
Tyre	ø200 pneumatic / Solid Rubber Tyre	ø400-8 pneumatic / Solid Rubber Tyre	ø400-8 pneumatic / Solid Rubber Tyre	ø500-8 pneumatic / Solid Rubber Tyre	ø500-8 pneumatic / Solid Rubber Tyre	ø500-8 pneumatic / Solid Rubber Tyre	ø500-8 pneumatic / Solid Rubber Tyre	ø500-8 pneumatic / Solid Rubber Tyre	ø500-8 pneumatic / Solid Rubber Tyre	ø500-8 pneumatic / Solid Rubber Tyre

Note: There may be any specification/dimensional change. If these specifications are critical, the proposed application should be discussed.